



Clean Quiet Radiant Heat When & Where You Need It!

DISCOVER THE
















PROFESSIONAL DIESEL FIRED XL 6

- Fuel: Kerosene / Diesel #1, #2
- Effective heating regardless of rainy or windy weather
- · Possibility to heat a limited area
- · Easy to operate
- Reliability
- Great mobility
- Fast heat-up
- More fuel efficient than heating systems



SPECIFICATIONS		XL 6
Fuel		kerosene/diesel #1, #2
Heating power	Btu/hr	58,000
Fuel consumption	gal/hr	0.4
Thermostat control		included
Power supply	V/Hz	110-120/60
Rated current	Amps	1.25
Run Time	hr	7 or more
Tank capacity	gal	3
Packaging dimension (I x w x h)	inches	23.6 x 14.9 x 22.83
Net / gross weight	lb	39/44
Pallet	pcs	12

IMPORTANT:

Ventilation of the room is necessary to prevent a deficiency in oxygen supply.

PORTABLE INFRARED HEATER





- No air flow
- Low noise
- Overheat themostat
- Tip-over switch
- Multi function display
- Digital thermostat on board
- Electronic flame control
- · Standard photocell cut off
- · Electronic cooling system
- Solenoid fuel pump
- Double electrode ignition
- Fuel level gauge
- Double fuel filter
- Combustion chamber in ceramic fiber
- Easy maintenance

Optional 12 volt DC to 115 volt AC invertor enables use when no 115 volt power available



On board thermostat with digital display



XL 6 trolley







MC5®



MCS ITALY: Via Tione 12, 37010 Pastrengo (VR), Italy, (0039) 045 6770533 -

MCS CENTRAL EUROPE: ul. Magazynowa 5a, 62-023 Gądki, Poland, (0048) 61 654 4000

MCS RUSSIA: Transportnaya 22/2, 142802, Stupino, Moscow region, Russia, (007) 495 642 444 8

MCS CHINA: Unit A1, No. 1515 Jinshao Rd, Baoshang Industrial Zone, Shanghai, 200949, (0086) 21 – 61486668

For further information, please contact your distributor:

Info@MCSHeater.com

Call 916 638-0828 For Your Nearest Dealer In United States or Canada

10/27/2014 Revised

Data, descriptions and pictures are for indication only and absolutely not binding.

not binding.

The Company reserves the right to modify or improve them without prior notice.